

# Tough Technology Products Ltd

## PRODUCT SAFETY DATA SHEET

### 1. Identification of the Substance/Preparation & Supplier.

**Product Name:** Tyre

**Product Type:** Silicone Solvent Blend

**Supplier:** Tough Technology Products Ltd, 379 Washway Road, Sale, Cheshire, M33 4FJ

**Emergency information:** Emergency phone number (Office hours only): 0161 9699939 / 07785257565  
Fax no: 0161 9699939

### 2. Hazards Identification.

**Hazard designation:**

F Flammable  
Xn Harmful

**Information pertaining to particular dangers for man and environment:**

R10: Flammable  
R65: Harmful: may cause lung damage if swallowed  
R66: Repeated exposure may cause skin dryness or cracking  
R67: Vapours may cause drowsiness or dizziness

**Classification system:**

The health and environmental hazards of this preparation have been assessed by the conventional method described in annex II and III of the preparations Directive 1999/45 EC.

### 3. Composition/Information on Ingredients.

**Dangerous components:**

Hazardous component:	EINECS	Cas No.	Index	Risk Phrases:	Concentration:
Petroleum Distillate	265-149-8	64742-48-9	Xn	R65, R66	>40%
Petroleum Distillate	265-151-9	64742-49-0	Xn	R11, R36, R66, R67	<40%
n-Hexane	203-777-6	110-54-3	F,Xn,N	R11, R48/20, R51/53	<1%

**Additional information:** For the wording of the listed risk phrases refer to section 16.

### 4. First Aid Measures.

**Immediate medical attention is required.**

**Eye Contact:** Flush with clean water for 15minutes. If irritation persists, obtain medical attention.

**Skin Contact:** Remove contaminated clothing. Wash off with soap and water. The application of skin reconditioning (emollient) cream, can be beneficial.

**Inhalation:** Remove to fresh air. If symptoms persist, seek medical advice.

**Ingestion:** Water to drink and rinse may be beneficial. **Aspiration Hazard. May cause rapid absorption via lungs, resulting in injury to other body systems. Do not induce vomiting without medical advice.**

TYRE	REVISION 0	09.10.2007	Page 1
------	------------	------------	--------

### 5. Fire Fighting Measures:

**Suitable Extinguishing Media:** Foam, Dry Powder, Co2, Sand, Earth, Fine Water Spray suitable. Fire exposed containers should be sprayed with water to keep cool and avoid bursting.

**Unsuitable Extinguishing Media for Reasons of Safety:** Water Jet.

**Special Hazards caused by the material, its products of combustion or flue gases:** Classified as flammable. If involved in fire, may evolve noxious and toxic fumes.

**Protective Equipment:** Self-contained breathing apparatus may be required.

## **6. Accidental Release Measures.**

**Personal safety precautions:** Remove ignition sources. Wear protective equipment. Keep unprotected persons away. Use protective clothing, chemical eye goggles and PVC or rubber gloves.

**Measures for environmental protection:** Prevent from spreading (e.g. by dusting a ring of chemical binder).

**Methods for cleaning/collecting:** Soak liquid in absorbent material and collect solids in a container. Wash down floor area as spillages can be slippery.

Dispose only in accordance with Local Authority regulations, via authorised waste disposal agent. Advice can be obtained from the Waste Regulation Authority whether special waste regulations apply to this product.

Use only in well ventilated areas.

## **7. Handling and Storage.**

### **Handling:**

**Information for safe handling:** Keep in tightly closed containers. Avoid contact with skin and eyes. Observe good standards of industrial hygiene. Take note of emission threshold.

### **Storage:**

**Requirements to be met by storerooms and containers:** Store between 10-35°C. Store in mild steel, stainless steel or polyethylene containers.

**Information about storage in a common storage facility:** Store in a cool dry place away from heat or sources of combustion.

**Specific Uses:** To be used as polish, release agent and vehicle trim enhancer.

## **8. Exposure Controls/Personal Protection.**

### **Exposure limit values:**

<u>Ingredient Name</u>		<u>8hr TWA</u>	<u>15min STEL</u>
Petroleum Distillate	WEL	5mg/m <sup>3</sup>	10mg/m <sup>3</sup>
n-Hexane	WEL	20ppm	

### **Occupational exposure controls:**

Respiratory Protection: Unlikely to be necessary. Avoid breathing mists or vapours.

Hand: PVC or rubber gloves are recommended.

Eyes: Safety eye goggles should be worn.

Skin: Use protective clothing. Remove contaminated clothing and wash with soap and water.

### **Environmental exposure controls:**

Dispose only in accordance with Local Authority regulations, via authorised waste disposal agent.

<b>TYRE</b>	<b>REVISION 0</b>	<b>09.10.2007</b>	<b>Page 2</b>
-------------	-------------------	-------------------	---------------

## **9. Physical and Chemical Properties.**

<b>Appearance:</b>	Water White Fluid
<b>Odour:</b>	Solvent/Perfume
<b>Boiling Range:</b>	70-250°C
<b>Flash Point:</b>	38°C
<b>Flammability:</b>	Flammable
<b>Solubility in Organics:</b>	Soluble in many
<b>Water Solubility:</b>	Insoluble
<b>Viscosity @ 40°C:</b>	<7.0 c/st
<b>Vapour Density(Water=100):</b>	>1
<b>Specific Gravity @ 20°C:</b>	0.950 typical
<b>Auto Ignition Temp:</b>	N/D
<b>Freezing Point:</b>	<0°C

## **10. Stability and Reactivity.**

**Conditions to Avoid:** Protect against naked flames, hot surfaces and other high temperature sources.

**Materials to Avoid:** Strong oxidising agents.

**Hazardous Decomposition Products:** Oxides of carbon, water vapour and unidentified organic and inorganic compounds, some of which may be toxic may be produced. Product is stable under normal conditions.

## **11. Toxicological Information.**

Eyes:	May give rise to irritation and stinging.
Skin:	Prolonged or repeated contact may lead to de-fatting of the skin, irritation & skin cracking.
Inhalation:	Excessive exposure to mists caused by atomising systems may cause irritation to eyes and respiratory tract, possible inflammation of the lungs. Breathing vapours may cause drowsiness, dizziness, nausea or intoxication.
Ingestion:	Aspiration Hazard. May cause lung damage if material gets into lungs after swallowing, breathing vapour/spray or vomiting swallowed material. Swallowing of small amounts is not likely to cause serious discomfort. If swallowed in larger quantities, may cause vomiting and diarrhoea.

## **12. Ecological Information.**

**Eco-toxicity:** There is no data available on the product itself. Product is expected to be hazardous to aquatic organisms. May cause long term adverse effects in the aquatic environment.

**Mobility:** The product should not be allowed to enter drains or watercourses or be deposited where it can affect ground or surface waters. Will leach into soil. Avoid transfer into the environment.

**Persistence and Degradability:** Expected to biodegrade slowly.

**Bio-accumulative Potential:** The product is not expected to bio-accumulate.

## **13. Disposal Recommendations.**

Product should be disposed of via an authorised waste disposal contractor in accordance with all local and national regulations.

Dispose of empty containers in accordance with local and national regulations.

Advice can be obtained from the Waste Regulation Authority whether special waste regulations apply to this product.

TYRE	REVISION 0	09.10.2007	Page 3
------	------------	------------	--------

## **14. Transport Information.**

**UN Label:**

**Land Transport ADR/RID:**


**UN No:** 1993  
**Class:** 3  
**Proper Shipping Name:** Flammable Liquid, NOS (Hydrocarbon Solvent)  
**Packing Group:** III  
**Marine Pollutant:** No  
**Tremcard:** 30G35  
**HI No:** 30  
**ADR Classification Code:** F1  
**Limited Quantities Code:** LQ7  
**Tunnel Restriction Code:** (D/E)

**Maritime Transport IMDG:**

**UN No:** 1993  
**Class:** 3  
**Proper Shipping Name:** Flammable Liquid, NOS (Hydrocarbon Solvent)  
**Packing Group:** III  
**Marine Pollutant:** No  
**EmS No:** 3-07

**15. Regulatory Information.****Designation according to EC guidelines:**

The product has been classified and labelled in accordance with EC Directives / Ordinance on Hazardous Materials (CHIP).

**Hazard Symbol:**

F  
Xn



Flammable  
Harmful

**Risk Phrases:**

R10: Flammable  
R65: Harmful: may cause lung damage if swallowed  
R66: Repeated exposure may cause skin dryness or cracking  
R67: Vapours may cause drowsiness or dizziness

**Safety Phrases:**

S23: Do not breathe vapour or spray  
S37: Wear suitable gloves  
S51: Use only in well ventilated places  
S62: If swallowed, do not induce vomiting, seek medical advice immediately and show this container or label

**National Regulations:****Regulations which may apply in event of accident:****Control of Major Accident Hazards (COMAH)**

Critical quantity values according to the regulations on accidents should be adhered to.

**16. Other Information.**

Do not mix with other chemicals.

The information provided in this data sheet has been compiled in accordance with the requirements of the Chemicals (Hazard information and packaging) Regulations 2002 (CHIP 3).

This data sheet does not constitute an assessment of the workplace risks as required under the provisions of the Health & Safety at Work act and the Control of Substances Hazardous to Health (COSHH).

**R-phrases relevant to the products hazardous ingredients:**

R11: Highly Flammable  
R36: Irritating to the eyes  
R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation  
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment  
R65: Harmful: may cause lung damage if swallowed  
R66: Repeated Exposure may cause skin dryness or cracking  
R67: Vapours may cause drowsiness and dizziness

**Training Advice:** Users should be trained in good industrial hygiene practise.

**Recommended Restrictions on Use:**

**Department issuing data specification sheet:** Health and Safety Department

**\*Date compared to the previous version altered.**

**Legal Disclaimer:**

The information supplied above is based upon the present state of our knowledge of the product at the time of publication. It is given in good faith and no warranty is implied with respect to the specification or quality of the product. The user must satisfy himself that the product is entirely suitable for his purpose.

<b>TYRE</b>	<b>REVISION 0</b>	<b>09.10.2007</b>	<b>Page 5</b>
-------------	-------------------	-------------------	---------------